

# Soot Volume Fraction Experimental Data from Ethylene-Hydrogen and LPG Nonpremixed Flames Stabilized on a Bluff Body Burner

**Contact person:** Prof Bassam Dally  
Email: [bassam.dally@adelaide.edu.au](mailto:bassam.dally@adelaide.edu.au)

**Credits:**

Data Collection: Dr Nader Qamar and Prof Bassam Dally  
Data Reduction: Dr Shaun Chan  
Data Analyses: A/Prof Zeyad Alwahabi and Prof Gus

Summary

This document provides a brief description of the soot data collected. Soot volume fraction was measured using the Laser-induced incandescence technique at various axial heights about the bluff-body. The bluff-body burner dimensions are  $B=50$  mm

and a concentric jet diameter ( $D_j$ )= 150 mm

$B$ )=50 mm

**FLAME CONDITIONS**

					Coflow Velocity (m/s)
Flame A	Ethylene: 1.000 Hydrogen: 0.000	74.2	30900	41.7	23
Flame B	Ethylene: 0.671 Hydrogen: 0.329	102.1	30800	41.9	23
Flame C	Ethylene: 0.487 Hydrogen: 0.513	130.7	30440	42.6	23
Flame D	LPG: 1.000	36.3	30474	32.0	23

**Fuel Composition:**

Ethylene – 99.0% purity  
Hydrogen – 99.0% purity  
LPG (molar)– 97.35% propane, 1.35% ethane, 1.20% butane, 0.07% nitrogen, and 0.03% carbon dioxide.

**MEASUREMENT TECHNIQUE**

Laser Induced Incandescence, LII:

A full description of the measurement technique has been presented in a previous publication Qamar et al. 2009. Briefly, the output of an Nd: YAG laser at 1064 nm was used for the LII excitation. The laser beam was shaped into a sheet with a vertical height of ~80 mm and a thickness of ~0.3 mm in the measurement region. The LII operating fluence was maintained at ~0.9 J/cm<sup>2</sup> throughout the experiment to ensure that the LII signal observed is independent of laser fluence variation.

The LII signal was detected through a 430 nm optical filter onto an intensified CCD (ICCD) camera. The gate width of the camera was set to ~40 ns and the timing was set to be prompt with respect to the LII excitation process. The LII signal was calibrated via laser beam extinction measurements.